

FICHA TÉCNICA

POLO S2

KU0021

CE UNI EN ISO 20345:2012 S2 SRC ESD CLASS 3

Low shoe, MICROWASH thickness 1,8-2,0 mm.

Highly perspiring and abrasion resistant fabric lining.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2001 for the electrical resistance **ESD class 3 (electric dissipative footwear)**


Size 34-49 Shoe weight Sz 42 gr. 460



Materials



Technologies



Sectors



ESD Areas



Food, Hospital and Hygiene



Hotels, Restaurants & Catering

Sole



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an **excellent anti-slipping product**.

This sole is called **Kube**, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole.

With thanks to these special characteristics Kube obtained the maximum certification against slipping: **jobs on inclined roofs** (UNI 11583:2015).

Antislipping Test Results

SRC		VERY GOOD
ANTI-SLIPPING SOLE		
SRA ceramic + NaLS	HEEL \geq 0,28 FLAT \geq 0,32	0,46 0,43
SRB steel + glycerol	HEEL \geq 0,13 FLAT \geq 0,18	0,30 0,29

Plus



MICRO WASH is a Chrome free material finished with perspiring polyurethanes.

Very light and perspiring, it is suitable for alimentary et hospital sectors.

It is also studied for people wearing the shoes for a lot of hours on wet surfaces.

It resists to acids, mostly oleic acid.

It is washable with water and neutral soap at 40°.